



Sprinter PSM Software

MY25+ Standard Program – Fleet

Commercial Vans PSM Support

Mercedes-Benz
Vans. Born to run.



Notice

Mercedes-Benz USA, LLC (“MBUSA”) acknowledges receipt of the Parameterizable Special Module (“PSM”) request and provides this bulletin in response thereto. MBUSA does not in any way warrant the accuracy of the information contained in this bulletin and reserves the right to modify or append this bulletin without prior notification. MBUSA disclaims all liability associated with the provision of this bulletin. The information contained in this bulletin has not been verified through testing and so is not intended to serve as a work instruction, but rather is intended merely to provide information for Upfitters to take into consideration before retrofitting or modifying a Mercedes-Benz Sprinter Van. Prior to making any modification to or installing any equipment in or on a Mercedes-Benz or Freightliner Sprinter, you should review and ensure compliance with all applicable laws and regulations; consult with MBUSA’s Vans Engineering Support for Upfitter Management for additional and updated information; and read the Body & Equipment Guidelines for Sprinter Model Series 907. The PSM software is a customized and tailored software solution designed for a specific customer application matched to a specific Sprinter model configuration.

Exception: Factory Options M53, MT4 and T57 have factory PSM software installed

Vans PSM Support Contacts:

For information or upfitter inquiries

please submit a request via our website:


www.UpfitterPortal.com

Software Specifications – Conversion to MY25 PSM


The following software package provides 3 input and 19 output functions for upfits related to fleet vehicles. The program provides access to muting the radio, activating hazard lights, and vehicle information such as door open status, gear status, vehicle ignition status, and light status.

Please note that not all inputs and outputs need to be used. Use only applicable inputs and outputs.

Additional info: EK1 – Auxiliary electrical connector under driver's seat




Terminal	U [V] / I [A]	wire color
1 st power with engine running	12V / 10A	blue/yellow
2 nd battery direct power	12V / 25A	red/gray
3 rd ignition power	12V / 15A	black/yellow



Parameterizable Special Module (PSM) Information – MY25 Module Change

Part	Part Number
Specification (Parameterizable Special Module)	A 447 900 40 23

Plug	Part Name	Description
1	2.8 mm MCP pins	Power Supply + Ground
2	2.8 mm MQP pins	Multi-function Outputs
3	0.63 mm MQS pins	Multi-function Inputs/Outputs
4	0.63 mm MQS pins	CAN/Body CAN



Input Specification

#	Input Signal	Connector	Pin	Max Amps	Output Type	Comments
5	Mute Radio	3	23	0.01A	Low	
6	Mute Radio ONLY When in 'R'	3	28	0.01A	Low	Input Active & Gear in 'R'
7	Hazard warning lights	3	39	0.01A	Low	

Low Side values supply Ground when activated and remove Ground when inactive.

High Side values supply +12V when activated and remove +12V when inactive.

Vehicle Power States	
Terminal	Common Name
30	Battery Power
30r	Timed Battery Power
31	Chassis Ground
15c	Key In Ignition (Ign. Position 0)
15r	Key On (Ign. Position 1)
15x	Accessory Power (Ign. Position 2)
15	Ignition*
50	Engine Cranking
61	Engine Running
* Active during 15x, 50, and 61	

Output Specification

#	Output Signal	Connector	Pin	Max Amps	Output Type	Comments
1	Rear Door Open	2	7	5A	High	
2	Any Door Open	2	5	10A	High	Driver/Passenger/Right Sliding/Rear Doors
3	Brake Lights	2	8	5A	High	
4	Ignition ON	2	12	10A	High	Terminal 15
5	Right Sliding Door Open	2	1	5A	High	
6	Right Turn Signal	2	10	5A	High	Constant Signal When Active
7	Left Turn Signal	2	11	5A	High	Constant Signal When Active
8	Vehicle Locked	3	31	0.5A	High	2 seconds signal
9	Cargo Doors Locked	3	32	0.5A	High	2 seconds signal
10	Vehicle Unlocked	3	21	0.5A	High	2 seconds signal
11	Driver Seat Belt OFF when Gear NOT in 'P'	3	26	0.5A	Low	
12	Accelerator Pedal Pressed > 80%	3	12	0.5A	Low	
13	Park Brake ON	3	3	1A	Low	
14	Vehicle Speed > 65 mph	3	2	0.5A	Low	
16	Cargo Doors Unlocked	3	22	0.5A	High	2 seconds signal
17	Passenger Door Open	3	13	1A	Low	
18	Driver Door Open	2	4	5A	High	
19	Gear in 'P'	2	6	5A	High	
20	Gear in 'R'	2	9	5A	High	

Low Side values supply Ground when activated and remove Ground when inactive.

High Side values supply +12V when activated and remove +12V when inactive.

Vehicle Power States	
Terminal	Common Name
30	Battery Power
30r	Timed Battery Power
31	Chassis Ground
15c	Key In Ignition (Ign. Position 0)
15r	Key On (Ign. Position 1)
15x	Accessory Power (Ign. Position 2)
15	Ignition*
50	Engine Cranking
61	Engine Running
* Active during 15x, 50, and 61	